



Aluminium Hydraulic tank for side mounting



**For further
information please contact
our sales team
Phone: +45 5766 0000
E-Mail: verkauf@bevola.dk**

New Hydraulic tank series

Aluminium Hydraulic tank fitted to the frame.
Designed especially to the market.

- Art. no. 574222:** 135 l, Alu incl. brackets & filter (Return filter 572027 140 l/min)
L 350x H 650x D 650 mm
- Art. no. 574224:** 150 l, Alu incl. brackets & filter (Return filter 572027 140 l/min)
L 400x H 650x D 650 mm
- Art. no. 574226:** 170 l, Alu incl. brackets & filter (Return filter 572031 250 L/min)*
L 450x H 650x D 650 mm
- Art. no. 574228:** 200 l, Alu incl. brackets & filter (Return filter 572031 250 L/min)*
L 520x H 650x D 650 mm
- Art. no. 574230:** 250 l, Alu incl. brackets & filter (Return filter 572031 250 L/min)*
L 650x H 650x D 650 mm
- Art. no. 574232:** 300 l, Alu incl. brackets & filter (Return filter 572031 250 L/min)*
L 800x H 650x D 650 mm. This tank is an order item.

The tank sizes 135 l and 150 l are equipped with a 2 ½" suction piece. They are also fitted with a Parker GLF 1 return filter with a maximum flow of 140 l/min. On top of the tank there are two 1"-BSP couplings on the ventilation filter.

The tank size 170 l is equipped with a 3" suction piece, the tanks with a volume of 200 l, 250 l and 300 l are equipped with two 3" suction pieces. They are also fitted with a Parker GLF 1 return filter with a maximum flow of 250 l/min. On top of the tank there are two 1½"-BSP couplings on the ventilation filter.

*The tanks with a volume of 170 l, 200 l, 250 l and 300 l can also be delivered with an alternative filter 572050, that has a maximum flow of 350 l/min.

**A/S BEVOLA
Huginsvej 22
DK - 4100 Ringsted
Phone: 57 66 00 00
E-mail: verkauf@bevola.dk
www.bevola.com**